



Product Model: 611P series		Quartz Dynamic Pressure Sensor		Version: A Date: 2022-5-6																																											
YMC 611P series, dynamic pressure sensor, is designed to measure low-level pressure activity under high static pressure. Features: • Sturdy construction • Small size and light • Quartz sensing • High sensitivity accelerometer 		<table><tr><th>Performance</th><th>611P60</th></tr><tr><td>Sensitivity</td><td>83.5 mV/MPa</td></tr><tr><td>Measurement Range</td><td>0-60 MPa</td></tr><tr><td>Resolution</td><td>0.015 kPa</td></tr><tr><td>Overload Capacity</td><td>120%</td></tr><tr><td>Non-linearity</td><td>≤1% F.S.</td></tr><tr><td>Hysteresis</td><td>≤1% F.S.</td></tr><tr><td>Repeatability</td><td>≤1% F.S.</td></tr><tr><td>Rise Time</td><td>≤2.0 μs</td></tr><tr><td>Resonant Frequency</td><td>≥200 kHz</td></tr><tr><td>Temperature Range</td><td>-40 ~ +121 °C</td></tr><tr><td>Excitation Voltage</td><td>+18~+28 VDC</td></tr><tr><td>Excitation Current</td><td>2 - 10 mA</td></tr><tr><td>Output Impedance</td><td><100 Ω</td></tr><tr><td>Output Bias Voltage</td><td>11±1.5 VDC</td></tr><tr><td>Sensing Element</td><td>Quartz</td></tr><tr><td>Size mm</td><td>As left figure</td></tr><tr><td>Weight</td><td>~15 g</td></tr><tr><td>Mounting</td><td>M10X1</td></tr><tr><td>Output Connector</td><td>M5</td></tr><tr><td>Housing Material</td><td>Stainless Steel</td></tr></table>		Performance	611P60	Sensitivity	83.5 mV/MPa	Measurement Range	0-60 MPa	Resolution	0.015 kPa	Overload Capacity	120%	Non-linearity	≤1% F.S.	Hysteresis	≤1% F.S.	Repeatability	≤1% F.S.	Rise Time	≤2.0 μs	Resonant Frequency	≥200 kHz	Temperature Range	-40 ~ +121 °C	Excitation Voltage	+18~+28 VDC	Excitation Current	2 - 10 mA	Output Impedance	<100 Ω	Output Bias Voltage	11±1.5 VDC	Sensing Element	Quartz	Size mm	As left figure	Weight	~15 g	Mounting	M10X1	Output Connector	M5	Housing Material	Stainless Steel		
		Performance	611P60																																												
		Sensitivity	83.5 mV/MPa																																												
		Measurement Range	0-60 MPa																																												
		Resolution	0.015 kPa																																												
		Overload Capacity	120%																																												
		Non-linearity	≤1% F.S.																																												
		Hysteresis	≤1% F.S.																																												
		Repeatability	≤1% F.S.																																												
		Rise Time	≤2.0 μs																																												
		Resonant Frequency	≥200 kHz																																												
		Temperature Range	-40 ~ +121 °C																																												
		Excitation Voltage	+18~+28 VDC																																												
		Excitation Current	2 - 10 mA																																												
		Output Impedance	<100 Ω																																												
		Output Bias Voltage	11±1.5 VDC																																												
		Sensing Element	Quartz																																												
		Size mm	As left figure																																												
		Weight	~15 g																																												
		Mounting	M10X1																																												
Output Connector	M5																																														
Housing Material	Stainless Steel																																														
		Typical static calibration error curve 																																													
		 扬州英迈克测控技术有限公司 YMC PIEZOTRONICS INC																																													
Accessories	1. Coaxial shielded cable 1ea 2m 2. Certificate of inspection 1ea			Addr.:No.47 Xiangyun Road Yangzhou China Post code:225009 Website:www.chinaymc.com E-mail:sales@chinaymc.com Tel.:0514-87960802 Fax:0514-87960681																																											
Remark																																															

